

**Description**

Fastener Length: 11/32", Thread: 10-32, Thread Length: 19/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS1123V1                            |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5305-00-501-9640                     |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N NAS1123V1 Specifications

|                                              |                                                              |
|----------------------------------------------|--------------------------------------------------------------|
| <b>Thread Class:</b>                         | 3a                                                           |
| <b>Thread Direction:</b>                     | Right-hand                                                   |
| <b>Thread Length:</b>                        | 0.251 Inches Minimum And 0.301 Inches Maximum                |
| <b>Fastener Length:</b>                      | 0.323 Inches Minimum And 0.353 Inches Maximum                |
| <b>Head Style:</b>                           | Pan                                                          |
| <b>Head Diameter:</b>                        | 0.357 Inches Minimum And 0.373 Inches Maximum                |
| <b>Head Height:</b>                          | 0.122 Inches Minimum And 0.133 Inches Maximum                |
| <b>Grip Diameter:</b>                        | 0.1885 Inches Minimum And 0.1895 Inches Maximum              |
| <b>Internal Drive Style:</b>                 | Cross Recess Type 1                                          |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches                                                 |
| <b>Grip Length:</b>                          | 0.052 Inches Minimum And 0.072 Inches Maximum                |
| <b>Thread Quantity Per Inch:</b>             | 32                                                           |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                                |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head                     |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip                                        |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                                     |
| <b>Material:</b>                             | Titanium Alloy Uns R54520 Overall                            |
| <b>Material Document And Classification:</b> | Nas621,comp 6al-4v Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf                                                         |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1123V1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.