

Description

Fastener Length: 1-11/32", Thread: 10-32, Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1123V17 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-586-1964 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS1123V17 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.276 Inches Nominal |
| Fastener Length: | 1.323 Inches Minimum And 1.353 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.306 Inches Minimum And 0.316 Inches Maximum |
| Head Height: | 0.103 Inches Minimum And 0.118 Inches Maximum |
| Grip Diameter: | 0.1881 Inches Minimum And 0.1887 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.052 Inches Minimum And 1.072 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1123 Professional/Industrial Association Standard |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1123V17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.