

# **P/N NAS1123V17**

## **Description**

Fastener Length: 1-11/32", Thread: 10-32, Thread Length: 1/4

\* Manufacturer certifications are shipped with your order EREE of charge

# Order this part online

#### **Additional Information**

SKU / Model: NAS1123V17

Minimum Qty (MOQ):

NSN: 5305-01-586-1964

ECCN: EAR99



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1123V17 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Nominal
Fastener Length:	1.323 Inches Minimum And 1.353 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.306 Inches Minimum And 0.316 Inches Maximum
Head Height:	0.103 Inches Minimum And 0.118 Inches Maximum
Grip Diameter:	0.1881 Inches Minimum And 0.1887 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.052 Inches Minimum And 1.072 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1123 Professional/industrial Association Standard

## **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1123V17">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1123V17</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1123V17">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1123V17</a> and selecting the