

**Description**

NAS1131-4 Close Tolerance Screw

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS11314                                  |
| Minimum Qty (MOQ):      | 20  |
| NSN:                    | 5305-01-038-1300                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1131-4 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.276 Inches Nominal   |
| <b>Fastener Length:</b>                               | 0.526 Inches Nominal   |
| <b>Head Style:</b>                                    | Pan  |
| <b>Head Diameter:</b>                                 | 0.256 Inches Minimum And 0.270 Inches Maximum                      |
| <b>Head Height:</b>                                   | 0.087 Inches Minimum And 0.097 Inches Maximum                      |
| <b>Grip Diameter:</b>                                 | 0.1365 Inches Minimum And 0.1375 Inches Maximum                    |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                                      |
| <b>Nominal Thread Diameter:</b>                       | 0.138 Inches   |
| <b>Grip Length:</b>                                   | 0.250 Inches Nominal   |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                      |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head                           |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads   |
| <b>Material:</b>                                      | Steel Overall  |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjc   |
| <b>Specification/standard Data:</b>                   | 80205-nas1131 Professional/industrial Association Standard         |

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/screw/NAS1131-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.