

Description

Fastener Length: 1-9/32", Thread: 10-32, Thread Length: 19/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS113316
Minimum Qty (MOQ):	10
NSN:	5305-00-060-4372
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1133-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.251 Inches Minimum And 0.301 Inches Maximum
Fastener Length:	1.261 Inches Minimum And 1.291 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1133 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1133-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.