

**Description**

corrosion resistant steel - length: 0.464", thread: 10-32, pan head machine screw - close tolerance - short thread - offset cruciform recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS1133E3P       |
| Minimum Qty (MOQ): | 10               |
| NSN:               | 5305-01-308-2900 |



## P/N NAS1133E3P Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.251 Inches Minimum And 0.301 Inches Maximum              |
| <b>Fastener Length:</b>                      | 0.449 Inches Minimum And 0.479 Inches Maximum              |
| <b>Head Style:</b>                           | Pan  |
| <b>Head Diameter:</b>                        | 0.357 Inches Minimum And 0.373 Inches Maximum              |
| <b>Head Height:</b>                          | 0.122 Inches Minimum And 0.133 Inches Maximum              |
| <b>Grip Diameter:</b>                        | 0.1885 Inches Minimum And 0.1895 Inches Maximum            |
| <b>Internal Drive Style:</b>                 | High-torque  |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches   |
| <b>Grip Length:</b>                          | 0.178 Inches Minimum And 0.198 Inches Maximum              |
| <b>Thread Quantity Per Inch:</b>             | 32   |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                              |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head                   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip                                      |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                                   |
| <b>Material:</b>                             | Iron Alloy 660 Overall                                     |
| <b>Material Document And Classification:</b> | Ams 5737 Assn Std Single Material Response Overall         |
| <b>Surface Treatment:</b>                    | Cadmium Overall  |
| <b>Thread Series Designator:</b>             | Unjf   |
| <b>Specification/standard Data:</b>          | 80205-nas1133 Professional/industrial Association Standard |

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1133E3P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.