

**Description**

corrosion resistant steel, length: 0.526", thread: 10-32, pan head machine screw, close tolerance, short thread, offset cruciform recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1133E4P                                |
| Minimum Qty (MOQ):      | 20  |
| NSN:                    | 5305-01-303-7411                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1133E4P Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.251 Inches Minimum And 0.301 Inches Maximum              |
| <b>Fastener Length:</b>                      | 0.511 Inches Minimum And 0.541 Inches Maximum              |
| <b>Head Style:</b>                           | Pan  |
| <b>Head Diameter:</b>                        | 0.357 Inches Minimum And 0.373 Inches Maximum              |
| <b>Head Height:</b>                          | 0.122 Inches Minimum And 0.133 Inches Maximum              |
| <b>Grip Diameter:</b>                        | 0.1885 Inches Minimum And 0.1895 Inches Maximum            |
| <b>Internal Drive Style:</b>                 | High-torque  |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches   |
| <b>Grip Length:</b>                          | 0.240 Inches Minimum And 0.260 Inches Maximum              |
| <b>Thread Quantity Per Inch:</b>             | 32   |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                              |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head                   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip                                      |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                                   |
| <b>Material:</b>                             | Iron Alloy 660 Overall                                     |
| <b>Material Document And Classification:</b> | Ams 5737 Assn Std Single Material Response Overall         |
| <b>Surface Treatment:</b>                    | Cadmium Overall  |
| <b>Thread Series Designator:</b>             | Unjf   |
| <b>Specification/standard Data:</b>          | 80205-nas1133 Professional/industrial Association Standard |

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1133E4P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.