

## Description

Fastener Length: 21/32", Thread: 10-32, Thread Length: 19/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS1133V6                            |
| Minimum Qty (MOQ):      | 10                                   |
| NSN:                    | 5305-00-420-6451                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | EAR99                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



## P/N NAS1133V6 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.251 Inches Minimum And 0.301 Inches Maximum            |
| <b>Fastener Length:</b>                      | 0.636 Inches Minimum And 0.666 Inches Maximum            |
| <b>Head Style:</b>                           | Pan  |
| <b>Head Diameter:</b>                        | 0.357 Inches Minimum And 0.373 Inches Maximum            |
| <b>Head Height:</b>                          | 0.122 Inches Minimum And 0.133 Inches Maximum            |
| <b>Grip Diameter:</b>                        | 0.1885 Inches Minimum And 0.1895 Inches Maximum          |
| <b>Internal Drive Style:</b>                 | Offset Cruciform (torque Set)                            |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches   |
| <b>Grip Length:</b>                          | 0.365 Inches Minimum And 0.385 Inches Maximum            |
| <b>Thread Quantity Per Inch:</b>             | 32   |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                            |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head                 |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip                                    |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                                 |
| <b>Material:</b>                             | Titanium Alloy Uns R54520 Overall                        |
| <b>Material Document And Classification:</b> | Nas 621,6al-4v Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf   |

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1133V6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.