



Military-Fasteners.com

P/N NAS1134-2

## Description

Fastener Length: 29/64", Thread: 1/4-28, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS11342                                  |
| Minimum Qty (MOQ):      | 25 EA                                     |
| NSN:                    | 5305-00-916-4909                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1134-2 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.316 Inches Minimum  |
| <b>Fastener Length:</b>                               | 0.426 Inches Minimum And 0.456 Inches Maximum   |
| <b>Head Style:</b>                                    | Pan   |
| <b>Head Diameter:</b>                                 | 0.424 Inches Minimum And 0.492 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.162 Inches Minimum And 0.175 Inches Maximum   |
| <b>Grip Diameter:</b>                                 | 0.2485 Inches Minimum And 0.2495 Inches Maximum   |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)   |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches  |
| <b>Grip Length:</b>                                   | 0.125 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>                      | 28  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads  |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  |
| <b>Material Document And Classification:</b>          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas1134 Professional/industrial Association Standard  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1134-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.