

**Description**

Fastener Length: 53/64", Thread: 1/4-28, Thread Length: 21/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1134V8
Minimum Qty (MOQ):	5
NSN:	5305-00-462-5132
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



\* See page 2 for technical characteristics

## P/N NAS1134V8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.291 Inches Minimum And 0.341 Inches Maximum
<b>Fastener Length:</b>	0.801 Inches Minimum And 0.831 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.473 Inches Minimum And 0.492 Inches Maximum
<b>Head Height:</b>	0.162 Inches Minimum And 0.175 Inches Maximum
<b>Grip Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Titanium Alloy Uns R54520 Overall
<b>Material Document And Classification:</b>	Nas 621,6al-4v Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1134V8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.