

Description

size: 9/16, thickness: 1/32", corrosion resistant steel, passivated finish, NAS1149 series washer


* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN960C916L](#)

SKU / Model:	NAS1149C0932R
Minimum Qty (MOQ):	100
NSN:	5310-01-421-4256
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1149C0932R Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.573 Inches Minimum And 0.578 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	1.057 Inches Minimum And 1.062 Inches Maximum
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1149 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1149C0932R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.