

Description

size: #6, thickness 1/64", corrosion resistant steel, passivated finish, NAS1149 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN960C6L](#)

| | |
|-------------------------|---|
| SKU / Model: | NAS1149CN616R |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5310-01-352-9591 |
| Schedule B: | 7318.22.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



* See page 2 for technical characteristics

P/N NAS1149CN616R Specifications

| | |
|---|--|
| Cross-sectional Shape Style: | Rectangular |
| Hole Diameter: | 0.139 Inches Minimum And 0.159 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Thickness: | 0.014 Inches Minimum And 0.018 Inches Maximum |
| Overall Diameter: | 0.370 Inches Minimum And 0.395 Inches Maximum |
| Material: | Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1149 Professional/industrial Association Standard |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1149CN616R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.