

**Description**

Size: 1/4", thickness 1/64", aluminum alloy (2024-t3), anodized finish, NAS1149 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AN960KD416L](#)

SKU / Model:	NAS1149D0416K
Minimum Qty (MOQ):	100
NSN:	5310-01-398-8745
Schedule B:	7616.10.8000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1149D0416K Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	0.255 Inches Minimum And 0.275 Inches Maximum
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Thickness:</b>	0.013 Inches Minimum And 0.019 Inches Maximum
<b>Overall Diameter:</b>	0.495 Inches Minimum And 0.520 Inches Maximum
<b>Material:</b>	Aluminum Alloy 2024 Overall And Aluminum Alloy 1230 Overall
<b>Material Document And Classification:</b>	Qq-a-250/5 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625, Cl 2 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1149 Professional/Industrial Association Standard

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1149D0416K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.