

**Description**

Size: 1/4" thickness: 1/32", aluminum alloy, anodized finish, NAS1149 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1149D0432K
Minimum Qty (MOQ):	100
NSN:	5310-01-352-9565
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N NAS1149D0432K Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.255 Inches Minimum And 0.275 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	0.495 Inches Minimum And 0.520 Inches Maximum
Material:	Aluminum Alloy 2024 Overall And Aluminum Alloy 1230 Overall
Material Document And Classification:	Qq-a-250/5,t3 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,class 3 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1149 Professional/industrial Association Standard

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1149D0432K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.