

P/N NAS1149D0916K

Description

Hole Diameter: 37/64", Diameter: 1-5/64", Thickness: 1/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1149D0916K

Minimum Qty (MOQ): 100

NSN: 5310-01-425-6247

Schedule B: 7616.10.9090

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1149D0916K Specifications

| Cross-sectional Shape Style: | Rectangular |
|--|---|
| Hole Diameter: | 0.568 Inches Minimum And 0.588 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Thickness: | 0.014 Inches Minimum And 0.018 Inches Maximum |
| Overall Diameter: | 1.057 Inches Minimum And 1.082 Inches Maximum |
| Material: | Aluminum Alloy 2024 Overall And Aluminum Alloy 1230 Overall |
| Material Document And Classification: | Qq-a-250/5 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Cl 2 Mil Spec Single Treatment Response Overall |

How to Order

Order this flat washer from our inventory online by visiting https://military-fasteners.com/washers/flat+washers/NAS1149D0916K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.