

Description

Size: 3/4", thickness 1/32", aluminum alloy (2024-t3), annodized finish (gray colored)

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[AN960KD1216L](#)

SKU / Model:	NAS1149D1216K
Minimum Qty (MOQ):	25
NSN:	5310-01-409-0902
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1149D1216K Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.755 Inches Minimum And 0.775 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.016 Inches Nominal
Overall Diameter:	1.307 Inches Minimum And 1.332 Inches Maximum
Material:	Aluminum Alloy 2024 Overall And Aluminum Alloy 1230 Overall
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Cl 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1149 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1149D1216K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.