

**Description**

Hole Diameter: 1-1/64", Diameter: 1-49/64", Thickness: 1/64", NAS1149 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1149D1616K
Minimum Qty (MOQ):	25
NSN:	5310-01-240-1817
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

# P/N NAS1149D1616K Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	1.005 Inches Minimum And 1.025 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.013 Inches Minimum And 0.019 Inches Maximum
Overall Diameter:	1.745 Inches Minimum And 1.770 Inches Maximum
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-250/5,t3 Or T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	A Type And 1 Grade And D Class

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1149D1616K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.