

Description

Hole Diameter: 1-21/64", Diameter: 2-1/16", Thickness: 5/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1149D2190K
Minimum Qty (MOQ):	25
NSN:	5310-01-444-7646
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1149D2190K Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	1.323 Inches Minimum And 1.328 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.083 Inches Minimum And 0.092 Inches Maximum
Overall Diameter:	2.057 Inches Minimum And 2.062 Inches Maximum
Material:	Aluminum Alloy 2024 Overall And Aluminum Alloy 1230 Overall
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Cl 1 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1149 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1149D2190K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.