

Description

size: #3, thickness 1/64", aluminum alloy (2024-t3), anodized finish (gray colored)

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[AN960KD3L](#)

SKU / Model:	NAS1149DN316K
Minimum Qty (MOQ):	100
NSN:	5310-00-183-4357
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

# P/N NAS1149DN316K Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.095 Inches Minimum And 0.115 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.013 Inches Minimum And 0.019 Inches Maximum
Overall Diameter:	0.245 Inches Minimum And 0.270 Inches Maximum
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall Or Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Overall Or Mil-a-8625 Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	43999-2w1 Manufacturers Standard

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1149DN316K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.