

**Description**

size: #5, thickness 0.042", aluminum alloy (2024-t3) - anodized finish (gray colored)

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1149DN542K
Minimum Qty (MOQ):	100
NSN:	5310-01-352-9569
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1149DN542K Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	0.130 Inches Minimum And 0.150 Inches Maximum
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Thickness:</b>	0.038 Inches Minimum And 0.046 Inches Maximum
<b>Overall Diameter:</b>	0.433 Inches Minimum And 0.458 Inches Maximum
<b>Material:</b>	Aluminum Alloy 2024 Overall And Aluminum Alloy 1230 Overall
<b>Material Document And Classification:</b>	Qq-a-250/5,t3 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,class 3 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1149 Professional/Industrial Association Standard

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1149DN542K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.