

Description

size: #5, thickness 0.042", aluminum alloy (2024-t3) - anodized finish (gray colored)

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1149DN542K |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5310-01-352-9569 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1149DN542K Specifications

| | |
|---|---|
| Cross-sectional Shape Style: | Rectangular |
| Hole Diameter: | 0.130 Inches Minimum And 0.150 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Thickness: | 0.038 Inches Minimum And 0.046 Inches Maximum |
| Overall Diameter: | 0.433 Inches Minimum And 0.458 Inches Maximum |
| Material: | Aluminum Alloy 2024 Overall And Aluminum Alloy 1230 Overall |
| Material Document And Classification: | Qq-a-250/5,t3 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,class 3 Mil Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1149 Professional/Industrial Association Standard |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1149DN542K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.