

# P/N NAS1149DN632K

Military-Fasteners.com

#### Description

Size: #6, thickness 1/32", aluminum alloy, annodized finish, NAS1149 series washer

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

AN	9	6(	)K	D6	

SKU / Model:	NAS1149DN632K
Minimum Qty (MOQ):	100
NSN:	5310-01-352-9561
ECCN:	EAR99
National Motor Freight:	161740, Maps / Charts Noi



## P/N NAS1149DN632K Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.139 Inches Minimum And 0.159 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	0.370 Inches Minimum And 0.395 Inches Maximum
Material:	Aluminum Alloy 2024 Overall And Aluminum Alloy 1230 Overall
Material Document And Classification:	Qq-a-250/5,t3 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, class 3 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1149 Professional/industrial Association Standard

### How to Order

Order this flat washer from our inventory online by visiting <u>https://military-fasteners.com/washers/flat+washers/NAS1149DN632K</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.