

**P/N NAS1151E4** 

Military-Fasteners.com

#### Description

Fastener Length: 17/32", Thread: 6-32, Thread Length: 19/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS1151E4
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-526-0466
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS1151E4 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.251 Inches Minimum And 0.301 Inches Maximum
Fastener Length:	0.511 Inches Minimum And 0.541 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.221 Inches Minimum And 0.279 Inches Maximum
Grip Diameter:	0.1365 Inches Minimum And 0.1375 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.138 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1151 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1151E4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.