

Description

Thread: 8-32, Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS115212
Minimum Qty (MOQ):	25
NSN:	5305-01-309-5456
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N NAS1152-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Nominal
Fastener Length:	1.011 Inches Minimum And 1.041 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.328 Inches Minimum And 0.337 Inches Maximum
Grip Diameter:	0.1621 Inches Minimum And 0.1627 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall
Material Document And Classification:	Mil-s-5626 Mil Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty li,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1152 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1152-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.