

Description

Thread: 8-32, Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS115212 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-01-309-5456 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1152-12 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.276 Inches Nominal |
| Fastener Length: | 1.011 Inches Minimum And 1.041 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.328 Inches Minimum And 0.337 Inches Maximum |
| Grip Diameter: | 0.1621 Inches Minimum And 0.1627 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.164 Inches |
| Grip Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Comp 4140 Overall Or Steel Comp 4340 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty li,cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1152 Professional/industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1152-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.