

P/N NAS1152-2

Military-Fasteners.com

Description

Fastener Length: 13/32", Thread: 8-32, Thread Length: 1/4", NAS1152 series screw

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS11522
Minimum Qty (MOQ):	100
NSN:	5305-00-816-4628
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1152-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Minimum
Fastener Length:	0.386 Inches Minimum And 0.416 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.280 Inches Minimum And 0.337 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1152-2 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1152-2</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.