

Description

Fastener Length: 13/32", Thread: 8-32, Thread Length: 19/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1152E2P |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-01-304-2728 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS1152E2P Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.251 Inches Minimum And 0.301 Inches Maximum |
| Fastener Length: | 0.386 Inches Minimum And 0.416 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.280 Inches Minimum And 0.337 Inches Maximum |
| Grip Diameter: | 0.1625 Inches Minimum And 0.1635 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.164 Inches |
| Grip Length: | 0.115 Inches Minimum And 0.135 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1152 Professional/industrial Association Standard |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1152E2P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.