

P/N NAS1152E6P

Description

Fastener Length: 21/32", Thread: 8-32, Thread Length: 19/64", NAS1152 series bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1152E6P

Minimum Qty (MOQ): 25

NSN: 5305-01-074-6846

Schedule B: 7318.15.6080

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N NAS1152E6P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.251 Inches Minimum And 0.301 Inches Maximum
Fastener Length:	0.636 Inches Minimum And 0.666 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.280 Inches Minimum And 0.337 Inches Maximum
Grip Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1152 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS1152E6P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.