

Description

Fastener Length: 15/32", Thread: 8-32, Thread Length: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS1152V3 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-127-5685 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N NAS1152V3 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.251 Inches Minimum And 0.301 Inches Maximum |
| Fastener Length: | 0.449 Inches Minimum And 0.479 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.280 Inches Minimum And 0.337 Inches Maximum |
| Grip Diameter: | 0.1625 Inches Minimum And 0.1635 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.164 Inches |
| Grip Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Nas 621 Comp 6al-4v Assn Std 1st Material Response Overall Or Ams 4928 Assn Std 2nd Material Response Overall |
| Thread Series Designator: | Unc |
| Specification/standard Data: | 80205-nas1152 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1152V3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.