

**Description**

Fastener Length: 15/32", Thread: 8-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1152V3A
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-339-0513
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1152V3A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.276 Inches Nominal
<b>Fastener Length:</b>	0.449 Inches Minimum And 0.479 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.280 Inches Minimum And 0.337 Inches Maximum
<b>Internal Drive Style:</b>	Torque Set
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Titanium Alloy Uns R56400
<b>Screw Material Document And Classification:</b>	Ams 4967 Assn Std Single Material Response
<b>Bearing Surface Of Head Surface Finish:</b>	32.0 Microinches
<b>Shank Surface Finish:</b>	32.0 Microinches
<b>Thread Surface Finish:</b>	32.0 Microinches
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas1152 Professional/Industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1152V3A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.