

Description

Fastener Length: 29/32", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS115310D |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-578-2252 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



P/N NAS1153-10D Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.276 Inches Nominal |
| Fastener Length: | 0.886 Inches Minimum And 0.916 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.328 Inches Minimum And 0.385 Inches Maximum |
| Grip Diameter: | 0.188 Inches Minimum And 0.189 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.625 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Part Name Assigned By Controlling Agency: | Screw Machine Flat 100 Degrees Head Close Tolerance Short Thread Offset Cruciform 160 Ksi |
| Special Features: | Item Has Drilled Shank |
| Material: | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1153-10D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.