

P/N NAS1153-11D

Description

Fastener Length: 31/32", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS115311D

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-578-4109

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N NAS1153-11D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Minimum
Fastener Length:	0.949 Inches Minimum And 0.979 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.328 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.688 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw Machine Flat 100 Degrees Head Close Tolerance Short Thread Offset Cruciform 160 Ksi (screw Close Tolerance)
Special Features:	Item Has Drilled Shank
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1153-11D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1153-11D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/MAS1153-11D and selecting the quantity you want then click "add to cart".