

P/N NAS1153-26

Description

Fastener Length: 1-29/32", Thread: 10-32, Thread Length: 19/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS115326

Minimum Qty (MOQ): 50

NSN: 5305-01-072-9144

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1153-26 Specifications

3a
Right-hand
0.251 Inches Minimum And 0.301 Inches Maximum
1.886 Inches Minimum And 1.916 Inches Maximum
Flat Countersunk
0.328 Inches Minimum And 0.385 Inches Maximum
0.1885 Inches Minimum And 0.1895 Inches Maximum
Offset Cruciform (torque Set)
0.190 Inches
1.615 Inches Minimum And 1.635 Inches Maximum
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
99.0 Degrees Minimum And 101.0 Degrees Maximum
32.0 Microinches Grip
32.0 Microinches Threads
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas1153 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1153-26 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1153-26 and selecting the quantity you