

Description

Fastener Length: 2-9/32", Thread: 10-30, Thread Length: 19/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS115332
Minimum Qty (MOQ):	5
NSN:	5305-00-450-7476
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1153-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.251 Inches Minimum And 0.301 Inches Maximum
Fastener Length:	2.261 Inches Minimum And 2.291 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.328 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.990 Inches Minimum And 2.010 Inches Maximum
Thread Quantity Per Inch:	30
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1153-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.