

Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS11536D |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-562-7569 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N NAS1153-6D Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.276 Inches Nominal |
| Fastener Length: | 0.651 Inches Nominal |
| Head Style: | Flat Countersunk Undercut |
| Head Diameter: | 0.376 Inches Minimum And 0.385 Inches Maximum |
| Head Height: | 0.090 Inches Nominal |
| Grip Diameter: | 0.188 Inches Minimum And 0.189 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.375 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams6382 Assn Std 1st Material Response Or Ams6414 Assn Std 2nd Material Response Or Ams6415 Assn Std 3rd Material Response Or Ams6484 Assn Std 4th Material Response Or Ams6322 Assn Std 5th Material Response Or Ams6325 Assn Std All Material Responses Or Ams6327 Assn Std 6th Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1153-6D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.