

**Description**

Fastener Length: 1-3/32", Thread: 10-32, Thread Length: 19/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1153E13P                               |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5305-01-101-4838                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1153E13P Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.251 Inches Minimum And 0.301 Inches Maximum                 |
| <b>Fastener Length:</b>                               | 1.073 Inches Minimum And 1.103 Inches Maximum                 |
| <b>Head Style:</b>                                    | Flat Countersunk  |
| <b>Head Diameter:</b>                                 | 0.328 Inches Minimum And 0.376 Inches Maximum                 |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum               |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                                 |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 0.802 Inches Minimum And 0.822 Inches Maximum                 |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                 |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.1 Degrees Maximum                |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head                      |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                                      |
| <b>Material:</b>                                      | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b>          | Ams5737 Assn Std Single Material Response Overall             |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                          |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas1153 Professional/industrial Association Standard    |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153E13P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.