

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1153E14P |
| Minimum Qty (MOQ): | 25 EA |
| NSN: | 5305-01-492-2093 |



P/N NAS1153E14P Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.276 Inches Nominal |
| Fastener Length: | 1.151 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.328 Inches Nominal |
| Grip Diameter: | 0.188 Inches Minimum And 0.189 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.875 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Ty II, Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153E14P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.