

## **P/N NAS1153E15**

## **Description**

Fastener Length: 1-7/32", Thread: 10-32, Thread Length: 19/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1153E15
Minimum Qty (MOQ):	10
NSN:	5305-01-045-2468
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1153E15 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.251 Inches Minimum And 0.301 Inches Maximum
Fastener Length:	1.199 Inches Minimum And 1.229 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.328 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.928 Inches Minimum And 0.948 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1153 Professional/industrial Association Standard

## **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153E15">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153E15</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.