

P/N NAS1153E15P

Description

Fastener Length: 1-7/32", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1153E15P
Minimum Qty (MOQ):	25 EA
NSN:	5305-01-491-9054
Schedule B:	7318.15.6080
FCCN:	9A991



^{*} See page 2 for technical characteristics

P/N NAS1153E15P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Nominal
Fastener Length:	1.199 Inches Minimum And 1.229 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.328 Inches Minimum
Head Height:	0.015 Inches Nominal
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw, Machine-flat
Screw Material:	Steel Corrosion Resisting
Head Surface Treatment:	Cadmium
Screw Surface Treatment:	Cadmium
Shank Surface Treatment:	Cadmium
Head Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response
Screw Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response
Shank Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153E15P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.