

Description

Fastener Length: 1-9/32", Thread: 12-32, Thread Length: 19/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1153E16
Minimum Qty (MOQ):	10
NSN:	5305-00-005-0643
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1153E16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.251 Inches Minimum And 0.301 Inches Maximum
Fastener Length:	1.261 Inches Minimum And 1.291 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.328 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.192 Inches
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas 1153 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153E16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.