

Description

Fastener Length: 1-23/32", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1153E23D |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-446-9873 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N NAS1153E23D Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.276 Inches Nominal |
| Fastener Length: | 1.694 Inches Minimum And 1.729 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.328 Inches Minimum And 0.385 Inches Maximum |
| Grip Diameter: | 0.1881 Inches Minimum And 0.1887 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Minimum Threads And 0.080 Inches Maximum Threads |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.428 Inches Minimum And 1.448 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.597 Inches Nominal Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1153 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153E23D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.