

**Description**

Fastener Length: 13/16", Thread: 10-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1153E9A
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-582-5443
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1153E9A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.276 Inches Nominal
<b>Fastener Length:</b>	0.838 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.328 Inches Minimum And 0.385 Inches Maximum
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
<b>Internal Drive Style:</b>	Torque-set Ribbed
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.552 Inches Minimum And 0.572 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	0.696 Inches Minimum First Hole And 0.736 Inches Maximum First Hole
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153E9A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.