

**Description**

Fastener Length: 29/32", Thread: 12-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1153V10                                |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5305-00-915-2210                          |
| Schedule B:             | 8108.90.3060                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi Sub1 |

NO IMAGE  
AVAILABLE

## P/N NAS1153V10 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.276 Inches Minimum  |
| <b>Fastener Length:</b>                      | 0.886 Inches Minimum And 0.916 Inches Maximum                       |
| <b>Head Style:</b>                           | Flat Countersunk  |
| <b>Head Diameter:</b>                        | 0.328 Inches Minimum And 0.385 Inches Maximum                       |
| <b>Grip Diameter:</b>                        | 0.1885 Inches Minimum And 0.1895 Inches Maximum                     |
| <b>Internal Drive Style:</b>                 | Offset Cruciform (torque Set)                                       |
| <b>Nominal Thread Diameter:</b>              | 0.192 Inches  |
| <b>Grip Length:</b>                          | 0.625 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>             | 32  |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                      | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Countersink Angle:</b>                    | 99.0 Degrees Minimum And 101.0 Degrees Maximum                      |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads  |
| <b>Material:</b>                             | Titanium Alloy Uns R54520 Overall                                   |
| <b>Material Document And Classification:</b> | Nas 621,6al-4v Assn Std Single Material Response Overall            |
| <b>Thread Series Designator:</b>             | Unjf  |
| <b>Specification/standard Data:</b>          | 80205-nas1153 Professional/Industrial Association Standard          |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153V10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.