

Description

Fastener Length: 1-19/32", Thread: 10-32, Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1153V21
Minimum Qty (MOQ):	5
NSN:	5305-00-920-0551
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS1153V21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Minimum
Fastener Length:	1.573 Inches Minimum And 1.603 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.328 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.312 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Nas 621,6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1153 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1153V21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.