

P/N NAS1153V36

Description

Fastener Length: 2-17/32", Thread Length: 19/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1153V36
Minimum Qty (MOQ): 10 EA

NSN: 5305-00-459-1183

Schedule B: 8108.90.3060

ECCN: 9A991

National Motor Freight: 136500, Metal Noi / Metal Alloys Noi



^{*} See page 2 for technical characteristics

P/N NAS1153V36 Specifications

Thread Class:	3a
Thread Length:	0.251 Inches Minimum And 0.301 Inches Maximum
Fastener Length:	2.511 Inches Minimum And 2.541 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Nas621,comp 6al-4v Assn Std Single Material Response Overall

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153V36 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153V36 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153V36 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153V36 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/nasen