

**Description**

Fastener Length: 3-1/32", Thread: 10-32, Thread Length: 19/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS1153V44                           |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5305-00-456-7823                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | EAR99                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



\* See page 2 for technical characteristics

## P/N NAS1153V44 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.251 Inches Minimum And 0.301 Inches Maximum            |
| <b>Fastener Length:</b>                      | 3.011 Inches Minimum And 3.041 Inches Maximum            |
| <b>Head Style:</b>                           | Flat Countersunk   |
| <b>Head Diameter:</b>                        | 0.328 Inches Minimum And 0.385 Inches Maximum            |
| <b>Grip Diameter:</b>                        | 0.1885 Inches Minimum And 0.1895 Inches Maximum          |
| <b>Internal Drive Style:</b>                 | Offset Cruciform (torque Set)                            |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches   |
| <b>Grip Length:</b>                          | 2.740 Inches Minimum And 2.760 Inches Maximum            |
| <b>Thread Quantity Per Inch:</b>             | 32   |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                            |
| <b>Countersink Angle:</b>                    | 100.0 Degrees Nominal                                    |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip                                    |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                                 |
| <b>Material:</b>                             | Titanium Alloy Uns R54520 Overall                        |
| <b>Material Document And Classification:</b> | Nas 621,6al-4v Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1153V44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.