

Description

Fastener Length: 2-45/64", Thread: 1/4-28, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS115438
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-509-3755
Schedule B:	7318.15.6080
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS1154-38 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.301 Inches Minimum And 0.331 Inches Maximum
Fastener Length:	2.676 Inches Minimum And 2.706 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.449 Inches Nominal
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
End Item Identification:	Rq-4a
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.365 Inches Minimum And 2.385 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw
Material:	Steel Comp 4140 Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1154-38> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.