

P/N NAS1154-6

Description

Fastener Length: 45/64", Thread: 1/4-28, Thread Length: 21/64", flat countersunk head, NAS1154 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS11546

Minimum Qty (MOQ): 50

NSN: 5305-00-816-1688

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS1154-6 Specifications

3a
Right-hand
0.291 Inches Minimum And 0.341 Inches Maximum
0.676 Inches Minimum And 0.706 Inches Maximum
Flat Countersunk
0.449 Inches Minimum And 0.507 Inches Maximum
0.2485 Inches Minimum And 0.2495 Inches Maximum
High-torque
0.250 Inches
0.365 Inches Minimum And 0.385 Inches Maximum
28
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
100.0 Degrees Nominal
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd
Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Unjf
80205-nas1154 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1154-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.