

P/N NAS1154E13

Description

Fastener Length: 1-9/64", Thread: 1/4-28, Thread Length: 5/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1154E13
Minimum Qty (MOQ):	10
NSN:	5305-01-429-9957
Schedule B:	7318.15.6080
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N NAS1154E13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.316 Inches Nominal
Fastener Length:	1.113 Inches Minimum And 1.143 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.497 Inches Minimum And 0.507 Inches Maximum
Grip Diameter:	0.248 Inches Minimum And 0.249 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.812 Inches Minimum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw, Machine-flat 100 Degree Head, Close Tolerance, Short Thread, Offset Cruciform
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1154 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1154E13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.