

Description

Fastener Length: 1-9/64", Thread: 1/4-28, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS1154E13 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-429-9957 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS1154E13 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.316 Inches Nominal |
| Fastener Length: | 1.113 Inches Minimum And 1.143 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.497 Inches Minimum And 0.507 Inches Maximum |
| Grip Diameter: | 0.248 Inches Minimum And 0.249 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.812 Inches Minimum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Part Name Assigned By Controlling Agency: | Screw, Machine-flat 100 Degree Head, Close Tolerance, Short Thread, Offset Cruciform |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1154 Professional/industrial Association Standard |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1154E13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.